



FUKU FK33-08

Basic Information

Volume

8m³

Water tank volume

450L

Wheelbase

1700+3175+1350mm

Displacement


7.8L

Overall mass

12200kg


Rated power

257Kw



Technical Specification

Volume	8
Chassis	FUKE
Engine	Yuchai
Overall mass	12,200kg
Max. permissible total mass	31000kg
Overall dimensions(L×W×H)	9700×2500×3980mm
Wheelbase	1700+3175+1350mm
Min. ground clearance	260mm
Min. turning diameter	22m
Fuel consumption per 100km	≤35L/100km
Braking distance (V0=30km/h)	≤ 10(full load); ≤9(no load)m
Bore*stroke	110×136mm×mm
Displacement	7.8L
Rated power/rpm	257/2100kW/rpm
Maximum torque	1400/1200-1600N·m/rpm
Emission standard	National VI
Feeding speed	≥ 8m ³ /min
Discharge speed	≥ 5m ³ /min
Discharge residual rate	< 0.5%
Slump range	50 ~ 210mm
Water tank volume	450L
Working pressure	0.35-0.38Mpa
Engine	WP8.350E61
Cab	CB318



*We follow the principle of continuous improvement Product performance parameters will be partially changed due to technical improvements without prior notice.

Contact us:

Phone/Whatsapp: +8613505697380

Email: fk002@fukebn.com/fuke7380@gmail.com